

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau




(43) International Publication Date
31 March 2005 (31.03.2005)

PCT

(10) International Publication Number
WO 2005/028862 A1

- (51) International Patent Classification⁷: **F03D 11/00**
- (21) International Application Number:
PCT/EP2003/010470
- (22) International Filing Date:
19 September 2003 (19.09.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (71) Applicant (for all designated States except US): **GENERAL ELECTRIC COMPANY** [US/US]; 1 River Road, Schenectady, NY 12345 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **BECKER, Markus** [DE/DE]; Waldeyerstr. 61, 48149 Muenster (DE). **SCHELLINGS, Vincent** [NL/NL]; Park de Kotten 160, NL-7522 EH Enschede (NL). **GAUCHEL, Peter** [DE/DE]; Schillerstr. 33a, 48143 Muenster (DE). **DELU-CIS, Nicolas** [FR/DE]; Emdener Str. 30, 48155 Muenster (DE).
- (74) Agents: **ZIMMERMANN, Gerd et al.**; Zimmermann & Partner, P.O. Box 330 920, 80069 Munich (DE).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: BEARING HOUSING



(57) Abstract: The present invention provides a bearing housing (10) for accommodating a rotor shaft (33) of a wind turbine. The bearing housing includes a flange (12) for connecting the bearing housing to a main frame (30) of the wind turbine. The flange having a connecting surface (51, 52) to be attached to the main frame. Thereby, at least parts of the connecting surface, when seen from the top of the bearing housing, would be located below the rotor shaft.

WO 2005/028862 A1

BEARING HOUSING

FIELD OF THE INVENTION

The invention relates to wind turbines. Further, the present invention relates to load transmitting components of wind turbines. Specifically, the present invention relates to bearing housings, main frames and wind turbines.

BACKGROUND OF THE INVENTION

Wind turbines provide a primary source of energy that can be converted into electricity and supplied to utility power grids. Conversion of wind energy to electrical energy is accomplished in a wind turbine by driving an electrical generator, commonly an AC induction generator. Recently, wind turbines have received increased attention as environmentally safe and relatively inexpensive alternative energy sources. With this growing interest, considerable efforts have been made to develop wind turbines that are reliable, efficient, and have increased availability.

However, at high wind speeds or for large wind turbines, the power captured from the wind by the rotor may lead to large loads acting on mechanical components. All components necessary for transmitting the loads to the tower are exposed to these large loads. Thus, components like the bearing housing and the main frame need to have a sufficient strength. Prior art systems typically increase the amount of material to withstand the loads. This may be considered an insufficient approach. Increasing the material strength, for example associates the disadvantage of an increased weight. Thus, there is a need to improve respective components.

BRIEF DESCRIPTION OF THE INVENTION

This object is attained by a bearing housing according to independent claims 1 and 3, a wind turbine according to independent claim 15 and a main frame according to independent claim 13.

Further advantages, features, aspects and details of the invention are evident from the dependent claims, the description and the accompanying drawings.

According to an aspect of the subject invention, a bearing housing for accommodating a rotor shaft of a wind turbine is provided. The bearing housing includes a flange for connecting the bearing housing to a main frame of the wind turbine. The flange has a connecting surface for attaching the bearing housing to the main frame. Thereby, at least parts of the connecting surface, when seen from the top of the bearing housing, is located below the rotor shaft position.

According to another aspect, a flange of a bearing housing has a connecting surface that can be averaged by a plane. The plane of the connecting surface is inclined with respect to the rotor shaft axis by an angle of at least 20° . Typically, this angle could be between 35° and 65° .

In the event of large loads acting on the rotor shaft of the wind turbine, these loads are received by the bearings of the rotor shaft and transferred to the bearing housing. In order to avoid singular load transmittal points, as conventionally used, a flange of the bearing housing as described above is provided. Thereby, the loads are more efficiently transmitted to the tower and the necessity for compensating increasing loads by using more material is reduced. This is achieved by the new design. Utilizing the above aspects, several advantages can be combined. On the one hand, the topology of the bearing housing body can be continued by the topology of the main frame body. This can be used to improve the load transmittal between the components. On the other hand, the flange can be constructed in a manner to reduce the shear rate between the components and to allow a separation of the bearing housing and the main frame. This favors manufacturing, transport and assembly. Thus, constructional aspects and load distribution aspects can be combined by inclining the flange surface.

According to another aspect, the bearing housing is essentially cast as a single component. Thereby, the load transmittal optimized shape can be manufactured without introducing unnecessary stress in the bearing housing body.

According to a further aspect, a bearing housing for accommodating a rotor shaft of a wind turbine is provided. The bearing housing includes a flange for connecting the bearing housing to a main frame of the wind turbine. The flange has a

connecting surface for attaching the bearing housing to the main frame. The flange of the bearing housing includes sections which have a curvature.

This aspect also allows for a larger connection surface area, which improves the load transmittal to the main frame.

According to another aspect, the bearing housing is suitable for accommodating two bearings. Typically, these bearings are a locating bearing and a floating bearing. Pooling the two bearings in one housing allows a compact wind turbine design.

According to another aspect, for wind turbines in the range of 1 MW and 4 MW, the flange has a thickness perpendicular to the connecting surface of below 120 mm. Typically, the thickness is between 60 mm and 100 mm. Reducing the loads acting on singular load transmittal points, allows for a reduced material strength. Thereby, the components weight can be reduced.

According to another aspect, a main frame is provided, which includes a flange for connecting the main frame with the bearing housing. The flange of the main frame is constructed to correspond to any of the features described with respect to the bearing housing above.

According to another aspect, a wind turbine is provided including a tower defining a z-axis, a rotor, and a rotor shaft defining an x-axis. The axis of the rotor shaft is located at a y-position y_s and the rotor shaft has a radius r . Further, a main frame and a bearing housing for accommodating the rotor shaft is included. The bearing housing includes a flange for connecting the bearing housing to the main frame. Thereby, the flange includes a connecting surface which is partly positioned at a z-position below the rotor shaft and at the same time at a y-position between y_s-r and y_s+r .

According to further aspects, the wind turbine includes any of the features described above with respect to the bearing housing of the wind turbine.

The invention is also directed to methods by which the described apparatus is manufactured. It includes method steps for manufacturing every feature of the apparatus.

BRIEF DESCRIPTION OF THE DRAWINGS

A full and enabling disclosure of the present invention, including the best mode thereof, to one of ordinary skill in the art, is set forth more particularly in the remainder of the specification, including reference to the accompanying figures wherein:

- Figure 1a shows a schematic side view of an embodiment according to the present invention;
- Figure 1b shows a view from the gear box side of the bearing housing of the embodiment of figure 1a;
- Figure 2 shows a schematic side view of a further embodiment of the present invention;
- Figure 3 shows a side view of a further embodiment of the present invention, wherein the bearing housing is connected to a respective main frame;
- Figure 4 shows a schematic side view of a further embodiment of a bearing housing;
- Figure 5 shows a three-dimensional view of a connecting surface of a flange of a bearing housing; and
- Figure 6 shows the set-up of a wind turbine.

DETAILED DESCRIPTION

Reference will now be made in detail to various embodiments of the invention, one or more examples of which are illustrated in the drawings. In the figures and the description that follows, like reference numerals refer to similar elements. Each example is provided by way of explanation of the invention, and is not meant as a limitation of the invention. For example, features illustrated or described as part of one embodiment can be used on or in conjunction with other embodiments to yield yet a further embodiment. It is intended that the present invention include such modifications and variations.

Fig. 1a and Fig. 1b show a bearing housing 10 according to one embodiment. Fig. 1a is a schematic side view of the bearing housing, whereas Fig. 1b is a view from plane A-A as indicated in Fig. 1a.

The bearing housing includes a cast iron body 11. Further, the bearing housing includes an opening 15 for accommodating the rotor shaft of the wind turbine. Reference numeral 13 denotes the rotor shaft axis.

The body 11 is formed to allow for an improved load transmittal of the loads captured via the rotor shaft to the main frame. The loads are transmitted to the main frame via flange 12.

As can be seen in Fig. 1b, the surface of the flange 12 exceeds in a curved form from the left side of the rotor shaft opening to the right side of the rotor shaft opening. Thereby, flange 12 is curved below rotor shaft opening 15. The curvature of the flange has a radius of at least 500 mm, typically between 1200 and 2000 mm. The shape of the flange 12 includes parts, which would be located below the rotor shaft, when seen from the top of the bearing housing.

Flange 12 is formed in one piece in order to increase the connecting surface area. Due to the increased surface area, the loads on the flange can be reduced. The loads are transmitted efficiently to the main frame as will be explained in more detail with respect to Fig. 3.

Prior art systems typically have one or two flanges on each side of the rotor shaft; the flanges are utilized to connect the bearing housing and the main frame. Thereby, discrete and localized spots need to be capable of transmitting the loads. The load distribution at the discrete spots required an increased material strength, especially for wind turbines producing several megawatts of power.

The enlarged area of the connection surface of the flange 12 of the bearing housing 10, as shown in Figs. 1a and 1b, has an improved characteristic of transmitting the loads to the main frame of the wind turbine. Thus, the flange thickness d can be reduced to a value between 70 and 90 mm.

Independently of specific embodiments, the area of the connecting surface can be increased. Typically, the area would be at least 1,5 m². This means, the area, as an example, could be between 2 m² and 4 m².

As can be further seen in Figs. 1a and 1b, a rotor stop body 14 is directly connected to the body 11 of bearing housing 10. Rotor stop body 14 is used to guide a stop mechanism to freeze the rotor in the event the rotor should not rotate. This could for example be the case in an off-state of the wind turbine during maintenance

or service events. In this embodiment, rotor stop body 14 and bearing housing body, as shown in Figs. 1a and 1b, are cast as one piece. The rotor stop body can, however, also be attached to the bearing housing.

Additional details can be seen from the embodiment shown in Fig. 2. Therein, a bearing housing 10, which is comparable to the bearing housing shown in Fig. 1a is shown. In the following the difference of Fig. 2 as compared to Fig. 1a will be described.

Fig. 2 shows two bearings included in the bearing housing 10. Locating bearing 21 and floating bearing 22 both hold the rotor shaft. Having the locating and the floating bearing in the bearing housing, a bearing can be avoided in the gear box. Thus, the two bearings being located close together (around 1m to 2m) within one housing consume less space. This results in the option of a more compact design of the wind turbine nacelle.

A further detail shown in Fig. 2, which can also be used independently of specific embodiments, is the assembling and maintenance opening 23. The bearing housing body 11 is cast with an opening 23, so that during assembly or maintenance the access to the bearings and the rotor shaft accommodated in the bearing housing is improved.

In the following reference is made to Fig. 3. Therein, a bearing housing 10, which is connected to a main frame 30 is shown. The bearing housing 10 includes the bearing housing body 11 and the flange 12. Further, a rotor stop body 14 is included. Rotor shaft 33 is located in the bearing housing.

The flange 12 of the bearing housing is connected to a corresponding flange 32 of the main frame. The main frame body 31 is shaped to also smoothly transmit the loads captured by the wind to the tower. The bearing housing body 11 together with the main frame body can be considered to define one topology. This topology is optimized for transmitting the loads to the tower head, which is connected to the main frame at the tower head flange 35.

The separation of the main frame body 31 and the bearing housing body 11 results, amongst others, in the following advantages. First, the two cast components can be more easily manufactured. Second, the individual components can be more easily transported. Third, the assembly and maintenance of the wind turbine is simplified.

Nevertheless, for small wind turbines the bearing housing and the main frame may be cast in one piece. Thereby, disturbance of the load transmittal could be decreased.

Assembling means 34, shown in Fig. 3, is used to assemble the gear box of the wind turbine to the main frame. Thereby, transverse forces acting on the gear box are also captured by the main frame. As a result, all forces or loads e.g. transmitted via the rotor shaft 33 can be transferred to the tower head over flange 35.

A further embodiment is shown in Fig. 4. The differences of this bearing housing as compared to Fig. 2 are described in the following. Bearing housing 10 of Fig. 4 has a flange, which includes two segments 12a and 12b. These segments have an offset. In order to define features of the segmented flange in a simplified manner, an average plane can be used. This plane is indicated in Fig. 4 with reference numeral 41.

The flange 12 and the connecting surface can be seen in more detail in Fig. 5. Fig. 5 shows a three-dimensional view from the bottom of flange 12. The flange of the bearing housing has a connecting surface, which can be described as follows. One the one hand, flange 12 includes a curved surface 51. One the other hand, the connecting surface includes two arm-like connecting surfaces 52 towards the inner area of the curve of surface 51.

In this embodiment, the connecting surface of the flange is continuous. That is the contact between the connecting surface of the flange and the connecting surface of a counterpiece flange is continuous. Thereby, this inventive aspect of a continuous connecting surface is to be understood as including minor discontinuities due to comparatively small grooves or recesses. The connecting surface in its entirety should be quasi-continuous.

All areas of the flange with a connecting surface have either one or two rows of openings for fastening means. Appropriate fastening means, like bolts or rivets or the like, can be passed through the openings and corresponding openings in the counterpiece of the flange of the bearing housing. The counterpiece would be a flange of the main frame. The curved portion of the connecting surface 51 has openings for fastening means which are positioned on a bend curve. The curve has a radius of at least 500 mm.

Fig. 5 shows a typical three rotor blade gear wind turbine; which may utilize the bearing housing described above. However, the bearing housing can be integrated to any horizontal rotor shaft wind turbine. The wind turbine includes a nacelle 102 mounted on a tower 100 supported by a foundation 128. The nacelle 102 houses a drive train for transmitting the rotation of a rotor 106 to a drive-shaft 118 of a generator 114. The drive train includes a rotor shaft 104 that connects the rotor 106 to a gearbox 112 in order to increase the rotation of the drive-shaft 118 of the generator 114. The drive-shaft 118 is often called the high-speed shaft and the rotor shaft 104 is known as the low-speed shaft. The rotor shaft 104 is connected to the rotor's hub 108, which generally supports three rotor blades 110. The gearbox can be optionally omitted thereby directly linking rotor 106 to generator 114. This configuration is known as a direct drive generator. The generator 114 feeds the generated electric energy into the power grid via power cables 124 with a grid connection 126 using electrical power devices such as a frequency converter and / or transformer. It is also possible that the electrical energy will be directly consumed by consumers without being fed to a public power grid.

Within Fig. 5, a z-axis defined by the tower is shown. The x-axis, which is defined by the rotor shaft, is essentially perpendicular to the z-axis. That is, the angle between the tower (z-axis) and the rotor shaft (x-axis) is between 90° and 100° . The y-axis is perpendicular to the x-z-plane. The bearing housing 10 can be described as follows with respect to these coordinates. If the rotor shaft axis is located at a y-position 0 and the rotor shaft has a radius r , then the flange of the bearing housing is at least partly located at a z-position below the rotor shaft. The same part is located at a y-position between $-r$ and r .

When an incoming air stream 116 turns the rotor 106, the wind's kinetic energy is converted into rotational energy of the rotor 106 and transmitted by the drive train to the generator, which finally converts the rotational energy into electric energy.

The efficiency of a wind turbine depends on many parameters including the orientation of the nacelle, or more specifically the location of the rotor plane with respect to the direction of the air stream. This is typically controlled by a yaw drive or azimuth-drive, which orients the nacelle into the wind. In modern wind turbines electrical and mechanical components form a yaw drive. More specifically, an electric high-speed drive motor is coupled by a gear reducer having a drive pinion gear engaging a bull gear. Usually the electric drive motor, the gear reducer, and the drive pinion gear are mounted on the nacelle's bedplate while the bull gear is fixed to

tower 100. For controlling the yaw-drive a wind-measuring sensor is used, which is capable of measuring the direction of the wind.

A similar configuration applies to a blade pitch drive 107 for adjusting the pitch angle of each of the rotor blades 106. This also dramatically affects the efficiency of the wind turbine.

For the three rotor blade wind turbine as described, the blade pitch system includes three blade pitch drives and three power control. Typically, the power control modules are arranged within the hub near the blade pitch drives.

Besides the rotational energy delivered to the generator and converted to electrical energy, other loads and forces act on the system. Loads and forces acting on the rotor shaft 104 are fed over the bearings in the bearing housing. The loads are transmitted over the tower head in the tower and the foundation 128. The load transmittal requires sufficient material strength of the components. Thereby, care needs to be taken to connecting flanges between individual components. The bearing housing 10 and main frame 30 as well as the flanges thereof, which has been described in detail with reference to Figs. 1a to 3, allow for an optimized load transmittal.

Having thus described the invention in detail, it should be apparent that various modifications can be made in the present invention without departing from the spirit and scope of the following claims.

CLAIMS

1. Bearing housing for accommodating a rotor shaft of a wind turbine, comprising:
a flange (12) for connecting the bearing housing to a main frame (30) of the wind turbine ;
the flange having a connecting surface to be attached to the main frame, whereby at least parts of the connecting surface, when seen from the top of the bearing housing, would be located below the rotor shaft (33).
2. Bearing housing according to claim 1, whereby
the flange (12) has a connecting surface that can be averaged by a plane (41);
and
whereby the plane is inclined with respect to the rotor shaft axis (13) by an angle of at least 20°.
3. Bearing housing for accommodating a rotor shaft of a wind turbine, comprising:
a flange for connecting the bearing housing (10) to a main frame (30) of the wind turbine;
the flange having a connecting surface that can be averaged by a plane (41), whereby the plane is inclined with respect to the rotor shaft axis (13) by an angle of at least 20°.
4. Bearing housing according to claim 3, whereby
at least parts of the connecting surface, when seen from the top of the bearing housing (10), would be located below the rotor shaft (33).
5. Bearing housing according to any of the preceding claims, whereby
the connecting surface (51, 52) is arranged in one plane.

6. Bearing housing according to any of the preceding claims, whereby the bearing housing is essentially a single cast iron component (11).
7. Bearing housing according to any of the preceding claims, whereby the flange (12) comprises openings (53) for fastening means, and whereby at least in sections, these openings are arranged along a curvature.
8. Bearing housing according to any of the preceding claims, whereby the bearing housing is suitable for accommodating two bearings (21, 22) for holding the rotor shaft.
9. Bearing housing according to any of the preceding claims, whereby the two bearings are a locating bearing (21) and a floating bearing (22).
10. Bearing housing according to any of the preceding claims, whereby the flange has a thickness (d) below 120 mm
11. Bearing housing according to any of the preceding claims, whereby the connecting surface of the flange of the bearing housing is continuous.
12. Bearing housing according to any of the preceding claims, whereby the connecting surface of the flange of the bearing housing has an area of at least 1.5 m².
13. Main frame of a wind turbine comprising:
a flange (32) with a bearing housing compatible connecting surface for connecting the main frame (30) to a bearing housing (10) of the wind turbine, whereby
at least parts of the bearing housing compatible connecting surface (33), when seen in a top view, would be located below a rotor shaft (33).

14. Main frame according to claim 15, whereby
the flange has a bearing housing compatible connecting surface that can be averaged by a plane (41),
whereby the plane is inclined with respect to the rotor shaft axis (13) by an angle of at least 20°.
15. Wind turbine comprising:
a tower (100) defining a z-axis;
a rotor (106);
a rotor shaft (104) defining an x-axis, the axis of the rotor shaft being located at a y-position y_s and the rotor having a radius r ;
a main frame (30);
a bearing housing (10) for accommodating the rotor shaft, the bearing housing comprising a flange (12) for connecting the bearing housing to the main frame;
wherein the flange comprises a connecting surface which is partly positioned at a z-position below the rotor shaft and at the same time at a y-position between y_s-r and y_s+r .
16. Wind turbine according to claim 17 whereby
the bearing housing comprises the features of any of claims 1 to 12

1/4




Fig. 1a




Fig. 1b

2/4




Fig. 2




Fig. 3

3/4




Fig. 4




Fig. 5

4/4




Fig. 6

INTERNATIONAL SEARCH REPORT

International Application No
PCT/EP 03/10470

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 F03D11/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 F03D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
E	DE 102 47 072 A (SKF GOETEBORG GOTENBURG AB) 22 April 2004 (2004-04-22) abstract columns 1-4 claim 6 figures	1-15
A	US 4 088 420 A (JACOBS MARCELLUS L ET AL) 9 May 1978 (1978-05-09) column 3, line 47 - line 66; figure 3	1, 3, 13, 15
A	US 4 757 211 A (KRISTENSEN EJLER) 12 July 1988 (1988-07-12) abstract column 3, line 44 - column 4, line 16; figure 2	1
----- -/--		

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *G* document member of the same patent family

Date of the actual completion of the international search

25 May 2004

Date of mailing of the international search report

01/06/2004

Name and mailing address of the ISA
European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Criado Jimenez, F

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 03/10470

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 1 291 521 A (TURBOWINDS N V S A) 12 March 2003 (2003-03-12) -----	
A	US 2003/080566 A1 (BECKER MARKUS ET AL) 1 May 2003 (2003-05-01) -----	
A	DE 41 04 454 C (DORSTENER MASCHINENFABRIK AG) 30 July 1992 (1992-07-30) -----	

INTERNATIONAL SEARCH REPORT

International Application No
PCT/EP 03/10470

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
DE 10247072	A	22-04-2004	DE 10247072 A1	22-04-2004
US 4088420	A	09-05-1978	CA 1068609 A1	24-12-1979
US 4757211	A	12-07-1988	NONE	
EP 1291521	A	12-03-2003	EP 1291521 A1	12-03-2003
US 2003080566	A1	01-05-2003	DE 10119428 A1	24-10-2002
			EP 1251306 A2	23-10-2002
DE 4104454	C	30-07-1992	DE 4104454 C1	30-07-1992
			DK 17792 A	15-08-1992
			NL 9200256 A	01-09-1992

Track Shipments/FedEx Kinko's Orders
Detailed Results[? Quick Help](#)

Tracking number	790845003508	Reference	06097.P063
Ship date	Oct 5, 2007	Destination	MUNSTER DE
		Service type	Priority Pak
		Weight	1.0 lbs.

Status Delivery exception

Date/Time	Activity	Location	Details
Oct 9, 2007	9:30 AM Delivery exception	DUESSELDORF DE	Incorrect address
Oct 8, 2007	3:04 PM Delivery exception	DUESSELDORF DE	Incorrect address
	9:02 AM On FedEx vehicle for delivery	DUESSELDORF DE	
	7:58 AM At local FedEx facility	DUESSELDORF DE	
Oct 7, 2007	1:30 AM Int'l shipment release	FRANKFURT DE	
	1:25 AM Arrived at FedEx location	FRANKFURT DE	
	1:25 AM In transit	FRANKFURT DE	Package available for clearance
Oct 6, 2007	5:35 AM Departed FedEx location	MEMPHIS, TN	
	2:33 AM Departed FedEx location	MEMPHIS, TN	
	12:58 AM Arrived at FedEx location	MEMPHIS, TN	
Oct 5, 2007	6:18 PM Left origin	SUNNYVALE, CA	
	5:39 PM Picked up	SUNNYVALE, CA	
	2:56 PM Package data transmitted to FedEx		

[E-mail results](#)[Track more shipments/orders](#)

Subscribe to tracking updates (optional)

Your Name: Your E-mail Address:

E-mail address	Language	Exception updates	Delivery updates
<input type="text"/>	English <input type="button" value="v"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input type="text"/>	English <input type="button" value="v"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input type="text"/>	English <input type="button" value="v"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input type="text"/>	English <input type="button" value="v"/>	<input type="checkbox"/>	<input type="checkbox"/>

Select format: ☒ HTML ☐ Text ☐ Wireless

Add personal message:

Not available for Wireless or non-English characters.


☐ By selecting this check box and the Submit button, I agree to these Terms and Conditions



CI 5090607/21/23

TofWgt: 1 LB

PM



CONSIGNEE COPY - PLEASE PLACE IN POUCH

LEGAL TERMS AND CONDITIONS OF FEDEX SHIPPING DEFINITIONS. On this Air Waybill, "we", "our", "us", and "FedEx" refer to Federal Express Corporation, its subsidiaries and branches and their respective agents, and independent contractors. The terms "you" and "your" refer to the shipper, its employees, principals and agents. If your shipment originates outside the United States, your contract of carriage is with the FedEx subsidiary, branch or independent contractor who originally accepted the shipment from you. The term "package" means any container or envelope that is accepted by us for delivery, including any such items tendered to our automated systems, meters, manifests or waybills. The term "shipment unit" means all packages which are tendered to and accepted by us on a single Air Waybill. **AIR CARRIAGE NOTICE.** For any international shipment under the Warsaw Convention, as amended, may be applicable. The Warsaw Convention limits FedEx's liability for loss, delay of, or damage to your shipment. The Warsaw Convention, as amended, limits FedEx's liability. For example in the U.S. liability is limited to \$9.09 per pound (20\$ per kilogram), unless a higher value for carriage is declared as described below and you pay any applicable applicable supplement charges. The interpretation and operation of the Warsaw Convention's liability limits may vary in each country. There are no specific stoppingplaces which are agreed to and FedEx reserves the right to route the shipment as it deems appropriate. **ROAD TRANSPORT NOTICE.** Shipments transported solely by road to or from a country which is a party to the Warsaw Convention or the Contract for the International Carriage of Goods ("CMR") are subject to the terms and conditions of the CMR, notwithstanding any other provision of this Air Waybill to the contrary. For those shipments transported solely by road, if a conflict arises between the provisions of the CMR and this Air Waybill, the terms of the CMR shall prevail. **LIMITATION OF LIABILITY.** If not governed by the Warsaw Convention, the CMR, or other international treaties, laws, other government regulations, orders or requirements, FedEx's maximum liability for damage, loss, delay, shortage, misdelivery, nondelivery, misinformation or failure to provide information in connection with your shipment is limited by this Agreement and the terms and conditions of the contract of carriage. FedEx will not be liable for the contract of carriage set forth in the applicable FedEx Service Guide or its equivalent to determine the contractual limitation. FedEx does not provide additional insurance, but you may pay an additional charge for each additional U.S. \$100 (or equivalent local currency for the country of origin) of declared value for carriage. If a higher value for carriage is declared as described above, your additional charge will be the lesser of the declared value for carriage or your actual damages. **LIABILITIES NOT ASSUMED. IN ANY EVENT, FEDEX WON'T BE LIABLE FOR ANY LOSS OF PROFITS OR CONSEQUENTIAL DAMAGES.** **WHETHER DIRECT, INDIRECT, INCIDENTAL, SPECIAL OR CONSEQUENTIAL IN EXCESS OF THE DECLARED VALUE FOR CARRIAGE (INCLUDING BUT NOT LIMITED TO LOSS OF INCOME OR PROFITS; ACTUAL VALUE OF THE SHIPMENT, IF LOWER, WHETHER OR NOT FEDEX HAD ANY KNOWLEDGE THAT SUCH DAMAGES MIGHT BE INCURRED.** FedEx won't be liable for your acts or omissions, including but not limited to incorrect declaration of cargo, improper or insufficient packaging, securing, marking or addressing of the shipment, or for the acts or omissions of the recipient or anyone else with an interest in the shipment or violation of the terms of this agreement. FedEx won't be liable for damage, loss, delay, shortage, misdelivery, nondelivery, misinformation or failure to provide information in connection with shipments of cash, currency or prohibited items or in instances beyond our control, such as acts of God, perils of the air, weather conditions, mechanical delays, acts of public enemies, war, strike, civil commotion, or acts or omissions of public authorities and health officials) with actual or apparent authority. **NO WARRANTY.** We make no warranties, express or implied. **CLAIMS FOR LOSS, DAMAGE OR DELAY. ALL CLAIMS MUST BE MADE IN WRITING AT THE STRICT TIME LIMITS. SEE OUR TARIFF, APPLICABLE FEDEX SERVICE GUIDE, OR STANDARD CONDITIONS OF CARRIAGE FOR DETAILS.** The Warsaw Convention provides specific written claims procedures for delay or non-delivery of your shipment. Moreover, the interpretation and operation of the Warsaw Convention's claims provisions may vary in each country. Refer to the Convention to determine the claims period for your shipment. The right to damages against us shall be extinguished unless an action is brought within two years, as set forth in the Convention. FedEx is not obligated to act on any claim until all transportation charges have been paid in full. The amount may not be deducted from the transportation charges. If the recipient accepts the shipment without noting any damage on the delivery record, FedEx will assume the shipment was delivered in good condition. To consider a claim for damage, the contents, original shipping carton and packing must be made available to us for inspection. **MANDATORY LAW.** Insofar as any provision contained or referred to in this Air Waybill is contrary to any applicable international treaties, laws, government regulations, orders or requirements such provisions shall remain in effect as a part of our agreement to the extent that it is not overridden. The invalidity or unenforceability of any provisions shall not affect any other part of this Air Waybill. Unless otherwise indicated, **FEDERAL EXPRESS CORPORATION, 2005 Corporate Avenue, Memphis, TN 38132, USA,** is the first carrier of the shipment. Email address located at www.fedex.com.